



DEESTONE

MOVE THE WORLD

ABOUT **DEESTONE**

DEESTONE was founded in 1977 by Mr. Suvit Vongsariyavanich. The company's vision is to manufacture quality tires for vehicles. Deestone's business philosophy "Integrity, Honesty, and Accountability" have resulted our company with worldwide reputation, qualifies with the global standards and trusted by more than 120 countries. With over 40 years of experience Deestone has been producing quality tires, while continuously developing every product to the highest standard. The use of new technology has allowed Deestone to create innovations that it meets specific application and use, which answers market demand. Deestone also concerns about environmental factors making our company environmental friendly. We ensure that all of our standard certification is up-to-date. All of our goals are to make our customers trust and proud when using our products.

All products of company serves various market demand which consist of high standard of production and certified with global standards. Deestone Group offers the after sales service to customers, with social responsibilities and warranty on the quality of company's products through all channel of communication with completely and clearly information. Product and brand image have been developing for highest customer satisfaction. We develop and produce quality tires for all segments of vehicles to be a part of your journey.





CONTENT

ABOUT US 02

PCR-UHP 04

LT-SUV 09

PCR-UHP

NAKARA R201

NAKARA R202

NAKARA R301

PATTERN NAME	SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		INFLATION PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(Psi)	(kPa)	TREAD.	TRAC.	TEMP.
R201	50	225/50R17	94	H	BSW	7.0	6.5 - 7.5	658	233	7.9	670	1480	44	300	500	A	A
	55	215/55R17	94	H	BSW	7.0	6.5 - 7.5	668	226	7.9	670	1480	44	300	500	A	A
		205/55R16	91	H	BSW	6.5	6.0 - 7.0	632	214	7.9	615	1355	44	300	500	A	A
	60	185/60R14	82	H	BSW	5.5	5.0 - 6.0	578	189	8.1	475	1047	44	300	500	A	A
		195/60R15	88	V	BSW	6.0	5.5 - 6.5	615	201	7.8	560	1234	44	300	500	A	A
		205/60R15	91	H	BSW	6.0	5.5 - 6.5	627	209	7.9	615	1355	44	300	500	A	A
		215/60R16	95	H	BSW	6.5	6.0 - 7.0	664	221	7.9	690	1520	44	300	500	A	A
		185/60R15	84	H	BSW	5.5	5.0 - 6.0	603	189	7.9	500	1100	44	300	500	A	A
		215/60R15	94	H	BSW	6.5	6.0 - 7.0	639	221	7.9	670	1480	44	300	500	A	A
		225/60R15	96	H	BSW	6.5	6.0 - 7.0	651	228	7.9	710	1565	44	300	500	A	A
		205/60R16	92	H	BSW	6.0	5.5 - 6.5	652	209	7.9	630	1390	44	300	500	A	A
		225/60R16	98	H	BSW	6.5	6.0 - 7.0	676	228	7.9	750	1655	44	300	500	A	A
		235/60R16	100	H	BSW	7.0	6.5 - 7.5	688	240	7.9	800	1765	44	300	500	A	A
	65	195/60R14	86	T	BSW	6.0	5.5 - 6.5	590	201	7.9	530	1160	44	300	500	A	A
		165/65R13	77	T	BSW	5.0	4.5 - 5.5	544	170	7.6	412	908	44	300	500	A	A
		175/65R14	82	H	BSW	5.0	4.5 - 5.5	584	177	7.8	475	1047	44	300	500	A	A
		185/65R14	86	H	BSW	5.5	5.0 - 6.0	596	189	7.8	530	1168	44	300	500	A	A
		185/65R15	88	H	BSW	5.5	5.0 - 6.0	621	189	7.8	560	1234	44	300	500	A	A
		215/65R15	96	H	BSW	6.5	6.0 - 7.0	661	221	7.9	710	1565	44	300	500	A	A
		195/65R15	91	H	BSW	6.0	5.5 - 6.5	635	201	7.9	615	1355	44	300	500	A	A
		205/65R15	94	H	BSW	6.0	5.5 - 6.5	647	209	7.9	670	1480	44	300	500	A	A
		215/65R16 XL	102	H	BSW	6.5	6.0 - 7.0	686	221	7.9	850	1875	50	340	500	A	A
		205/65R16	95	H	BSW	6.0	5.5 - 6.5	672	209	7.9	690	1520	44	300	500	A	A
	70	235/65R16	103	T	BSW	7.0	6.5 - 7.5	712	240	7.9	875	1930	44	300	500	A	A
		215/65R17	99	T	BSW	6.5	6.0 - 7.0	712	221	7.9	775	1710	44	300	500	A	A
		165/70R13	79	T	BSW	5.0	4.5 - 5.5	562	170	7.6	437	963	44	300	500	A	A
		175/70R13	82	T	BSW	5.0	4.5 - 5.5	576	177	8.1	475	1047	44	300	500	A	A
		175/70R14	84	H	BSW	5.0	4.5 - 5.5	602	177	7.8	500	1102	44	300	500	A	A
		185/70R13	86	H	BSW	5.5	5.0 - 6.0	590	189	7.8	530	1168	44	300	500	A	A
		185/70R14	88	H	BSW	5.5	5.0 - 6.0	616	189	7.8	560	1234	44	300	500	A	A
		195/70R14	91	H	BSW	6.0	5.5 - 6.5	630	201	8.1	615	1356	44	300	500	A	A
		205/70R14 XL	98	H	BSW	6.0	5.5 - 6.5	644	209	8.1	750	1655	50	340	500	A	A
215/70R15		98	H	BSW	6.5	6.0 - 7.0	683	221	8.1	750	1655	44	300	500	A	A	
80	155/80R12	77	T	BSW	4.5	4.0 - 5.0	553	157	7.9	412	910	44	300	500	A	A	
	165/80R15	87	T	BSW	4.5	4.0 - 5.0	645	165	7.9	545	1200	44	300	500	A	A	
R202	70	155/70R13	75	T	BSW	4.5	4.0 - 5.0	548	157	7.2	387	853	44	300	300	A	B
		155/70R12	73	T	BSW	4.5	4.0 - 5.0	523	157	6.9	365	805	44	300	240	A	A
	80	155/80R13	79	T	BSW	4.5	4.0 - 5.0	578	157	6.9	437	963	44	300	300	A	B
		165R13	82	S	BSW	4.5	4.0 - 5.0	594	165	7.6	475	1047	44	300	240	A	A
R301	50	195/50R15	82	V	BSW	6.0	5.5 - 6.5	577	201	7.6	475	1047	44	300	500	A	A
		225/55R16	95	V	BSW	7.0	6.5 - 7.5	654	233	7.8	690	1521	44	300	500	A	A
	55	215/55R16 XL	97	V	BSW	7.0	6.5 - 7.5	642	226	7.8	730	1609	50	340	500	A	A
		205/55R16	91	V	BSW	6.5	6.0 - 7.0	632	214	7.8	615	1356	44	300	500	A	A
		195/55R15	85	V	BSW	6.0	5.5 - 6.5	595	201	7.8	515	1135	44	300	500	A	A
	60	185/55R15	82	V	BSW	6.0	5.5 - 6.5	585	194	7.8	475	1047	44	300	500	A	A
		215/60R16	95	V	BSW	6.5	6.0 - 7.0	664	221	8.1	690	1521	44	300	500	A	A
	205/60R15	91	V	BSW	6.0	6.0 - 7.0	627	209	7.8	615	1356	44	300	500	A	A	
65	205/65R15	94	H	BSW	6.0	5.5 - 6.5	647	209	7.8	670	1477	44	300	500	A	A	
	195/65R15	91	H	BSW	6.0	5.5 - 6.5	635	201	7.8	615	1355	44	300	500	A	A	



CARRERAS R702

VINCENTE R203

PATTERN NAME	SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		INFLATION PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
R702	30	225/30ZR20 XL 85 W BSW	8.0	7.5 - 8.5	644	230	7.9	515	1140	50	340	500	A	A			
		235/30ZR22 XL 90 W BSW	8.5	8.0 - 9.0	701	242	8.0	600	1320	50	340	500	A	A			
		245/30ZR22 XL 92 W BSW	8.5	8.0 - 9.0	707	248	8.0	630	1390	50	340	500	A	A			
	35	245/35ZR20 XL 95 W BSW	8.5	8.0 - 9.0	680	248	7.9	690	1520	50	340	500	A	A			
		255/35ZR20 XL 97 W BSW	9.0	8.5 - 9.5	686	260	8.0	730	1610	50	340	500	A	A			
		265/35R18 XL 97 W BSW	9.5	9.0 - 10.0	643	271	8.0	730	1610	50	340	500	A	A			
	40	245/40ZR18 XL 97 W BSW	8.5	8.0 - 9.0	653	248	7.9	730	1610	50	340	500	A	A			
		205/40ZR17 XL 84 W BSW	7.5	7.0 - 8.0	596	212	7.9	500	1100	50	340	500	A	A			
		275/40ZR20 XL 106 W BSW	9.5	9.0 - 10.0	728	278	8.0	950	2095	50	340	500	A	A			
	45	235/45ZR17 XL 97 W BSW	8.0	7.5 - 8.5	644	236	7.9	730	1610	50	340	500	A	A			
		225/45ZR18 XL 95 W BSW	7.5	7.0 - 8.0	659	225	7.9	690	1520	50	340	500	A	A			
		245/45ZR18 XL 100 W BSW	8.0	7.5 - 8.5	677	243	7.9	800	1765	50	340	500	A	A			
		245/45ZR17 XL 99 W BSW	8.0	7.5 - 8.5	652	243	7.9	775	1710	50	340	500	A	A			
		235/45ZR18 XL 98 W BSW	8.0	7.5 - 8.5	669	236	7.9	750	1655	50	340	500	A	A			
		205/45ZR16 XL 87 W BSW	7.0	6.5 - 7.5	590	206	7.9	545	1200	50	340	500	A	A			
		205/45ZR17 XL 88 W BSW	7.0	6.5 - 7.5	616	206	7.9	560	1234	50	340	500	A	A			
		215/45ZR17 87 W BSW	7.0	6.5 - 7.5	626	213	7.9	545	1200	44	300	500	A	A			
	50	245/45ZR20 XL 103 W BSW	8.5	8.0 - 9.0	728	243	8.0	875	1930	50	340	500	A	A			
		205/50R17 89 V BSW	6.5	6.0 - 7.0	638	214	7.9	580	1280	44	300	500	A	A			
		195/50R15 82 V BSW	6.0	5.5 - 6.5	577	201	7.9	475	1050	44	300	500	A	A			
		265/50R20 XL 111 V BSW	8.5	8.0 - 9.0	774	277	8.6	1090	2405	50	340	500	A	A			
		205/50ZR16 87 W BSW	6.5	6.0 - 7.0	612	214	7.9	545	1200	44	300	500	A	A			
	55	225/55ZR17 97 W BSW	7.0	6.5 - 7.5	680	233	7.9	730	1610	44	300	500	A	A			
215/55ZR17 XL 98 W BSW		7.0	6.5 - 7.5	668	226	7.9	750	1655	50	340	500	A	A				
235/55R17 99 H BSW		7.5	7.0 - 8.0	690	245	7.9	775	1710	44	300	500	A	A				
235/55R19 101 V BSW		7.5	7.0 - 8.0	741	245	7.9	825	1820	44	300	500	A	A				
R203	55	185/55R15 82 V BSW	6.0	5.5 - 6.5	585	194	7.8	475	1050	44	300	540	A	A			
		165/55R14 72 H BSW	5.0	4.5 - 5.5	538	170	7.8	355	785	44	300	540	A	A			
	60	175/60R13 77 H BSW	5.0	4.5 - 5.5	540	177	7.8	412	910	44	300	540	A	A			
		175/60R15 81 H BSW	5.0	4.5 - 5.5	591	177	7.8	462	1020	44	300	540	A	A			
		205/60R14 88 H BSW	6.0	5.5 - 6.5	602	209	7.8	560	1230	44	300	540	A	A			
		185/60R15 84 H BSW	5.5	5.0 - 6.0	603	189	7.8	500	1100	44	300	540	A	A			
		185/60R14 82 H BSW	5.5	5.0 - 6.0	578	189	7.8	475	1050	44	300	540	A	A			
		165/60R13 73 H BSW	5.0	4.5 - 5.5	528	170	7.8	365	800	44	300	540	A	A			
	65	165/65R14 79 T BSW	5.0	4.5 - 5.5	570	170	7.8	437	965	44	300	540	A	A			
		175/65R14 82 H BSW	5.0	4.5 - 5.5	584	177	7.8	475	1050	44	300	540	A	A			
		175/65R15 84 H BSW	5.0	4.5 - 5.5	609	177	7.8	500	1100	44	300	540	A	A			
		185/65R14 86 H BSW	5.5	5.0 - 6.0	596	189	7.8	530	1160	44	300	540	A	A			
		185/65R15 88 H BSW	5.5	5.0 - 6.0	621	189	7.8	560	1230	44	300	540	A	A			
		165/65R13 77 T BSW	5.0	4.5 - 5.5	544	170	7.8	412	910	44	300	540	A	A			
		165/70R14 81 H BSW	5.0	4.5 - 5.5	588	170	7.8	462	1020	44	300	540	A	A			
		175/70R13 82 H BSW	5.0	4.5 - 5.5	576	177	7.8	475	1050	44	300	540	A	A			
	70	175/70R14 84 H BSW	5.0	4.5 - 5.5	602	177	7.8	500	1100	44	300	540	A	A			
		185/70R14 88 H BSW	5.5	5.0 - 6.0	616	189	7.8	560	1230	44	300	540	A	A			
		195/70R14 91 H BSW	6.0	5.5 - 6.5	630	201	7.8	615	1355	44	300	540	A	A			
		185/70R13 86 H BSW	5.5	5.0 - 6.0	590	189	7.8	530	1160	44	300	540	A	A			

VINCENTE R302

PREMIUM
TOURER RA01

PATTERN NAME	SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		INFLATION PRESSURE		UTQG			
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.	
R302	30	265/30ZR19 XL	93	W	BSW	9.5	9.0 - 10.0	643	271	7.9	650	1435	50	340	420	A	A	
	35	235/35ZR19 XL	91	W	BSW	8.5	8.0 - 9.0	647	241	7.9	615	1355	50	340	420	A	A	
	40	225/40ZR18 XL	92	W	BSW	8.0	7.5 - 8.5	637	230	7.9	630	1390	50	340	420	A	A	
		235/40ZR18 XL	95	W	BSW	8.5	8.0 - 9.0	645	241	7.9	690	1520	50	340	420	A	A	
	45	215/45ZR17	87	W	BSW	7.0	6.5 - 7.5	626	213	7.9	545	1200	44	300	420	A	A	
		225/45ZR17 XL	94	W	BSW	7.5	7.0 - 8.0	634	225	7.9	670	1480	50	340	420	A	A	
	50	225/45ZR18 XL	95	W	BSW	7.5	7.0 - 8.0	659	225	7.9	690	1520	50	340	420	A	A	
		195/50R15	82	V	BSW	6.0	5.5 - 6.5	577	201	7.9	475	1050	44	300	500	A	A	
		205/50ZR17 XL	93	W	BSW	6.5	6.0 - 7.0	638	214	7.9	650	1435	50	340	420	A	A	
		215/50ZR17	91	W	BSW	7.0	6.5 - 7.5	648	226	7.9	615	1355	44	300	420	A	A	
		225/50ZR17	94	W	BSW	7.0	6.5 - 7.5	658	233	7.9	670	1480	44	300	420	A	A	
		225/50R16	92	V	BSW	7.0	6.5 - 7.5	632	233	7.9	630	1390	44	300	500	A	A	
		195/50R16 XL	88	V	BSW	6.0	5.5 - 6.5	602	201	7.9	560	1230	50	340	500	A	A	
	55	185/55R15	82	V	BSW	6.0	5.5 - 6.5	585	194	7.9	475	1050	44	300	500	A	A	
		185/55R16	83	V	BSW	6.0	5.5 - 6.5	610	194	7.9	487	1070	44	300	500	A	A	
		195/55R15	85	V	BSW	6.0	5.5 - 6.5	595	201	7.9	515	1140	44	300	500	A	A	
		195/55R16	87	V	BSW	6.0	5.5 - 6.5	620	201	7.9	545	1200	44	300	500	A	A	
		205/55R15	88	V	BSW	6.5	6.0 - 7.0	607	214	7.9	560	1230	44	300	500	A	A	
		205/55R16	91	V	BSW	6.5	6.0 - 7.0	632	214	7.9	615	1355	44	300	500	A	A	
		215/55R16 XL	97	V	BSW	7.0	6.5 - 7.5	642	226	7.9	730	1610	50	340	500	A	A	
	60	215/55ZR17	94	W	BSW	7.0	6.5 - 7.5	668	226	7.9	670	1480	44	300	420	A	A	
		225/55R16 XL	99	V	BSW	7.0	6.5 - 7.5	654	233	7.9	775	1710	50	340	500	A	A	
		185/60R15	84	V	BSW	5.5	5.0 - 6.0	603	189	7.9	500	1100	44	300	500	A	A	
		195/60R15	88	V	BSW	6.0	5.5 - 6.5	615	201	7.9	560	1230	44	300	500	A	A	
		205/60R15	91	V	BSW	6.0	5.5 - 6.5	627	209	7.9	615	1355	44	300	500	A	A	
		205/60R16	92	V	BSW	6.0	5.5 - 6.5	652	209	7.9	630	1390	44	300	500	A	A	
		215/60R15	94	V	BSW	6.5	6.0 - 7.0	639	221	7.9	670	1480	44	300	500	A	A	
		215/60R16	95	V	BSW	6.5	6.0 - 7.0	664	221	7.9	690	1520	44	300	500	A	A	
		225/60R15	96	V	BSW	6.5	6.0 - 7.0	651	228	7.9	710	1565	44	300	500	A	A	
		225/60R16	98	V	BSW	6.5	6.0 - 7.0	676	228	7.9	750	1655	44	300	500	A	A	
	65	235/60R16	100	V	BSW	7.0	6.5 - 7.5	688	240	7.9	800	1765	44	300	500	A	A	
		215/60R17	96	H	BSW	6.5	6.0 - 7.0	690	221	7.9	710	1565	44	300	500	A	A	
	70	195/65R15	91	H	BSW	6.0	5.5 - 6.5	635	201	7.8	615	1355	44	300	500	A	A	
		205/65R15	94	H	BSW	6.0	5.5 - 6.5	647	209	7.9	670	1480	44	300	500	A	A	
	80	205/70R15	96	T	BSW	6.0	5.5 - 6.5	669	209	7.9	710	1565	44	300	500	A	A	
	RA01	80	155/80R13	79	H	BSW	4.5	4.0 - 5.0	578	157	7.9	437	965	44	300	500	A	A
		45	215/45ZR17	87	W	BSW	7.0	6.5 - 7.5	626	213	8	545	1200	44	300	500	A	A
			225/45ZR17	91	W	BSW	7.5	7.0 - 8.0	634	225	8	615	1355	44	300	500	A	A
			235/45ZR17 XL	97	W	BSW	8.0	7.5 - 8.5	644	236	8	730	1610	50	340	500	A	A
		50	245/45ZR17	95	W	BSW	8.0	7.5 - 8.5	652	243	8	690	1520	44	300	500	A	A
			195/50R16	84	V	BSW	6.0	5.5 - 6.5	602	201	8	500	1100	44	300	500	A	A
		55	215/50ZR17	91	W	BSW	7.0	6.5 - 7.5	648	226	8	615	1355	44	300	500	A	A
			225/50ZR17 XL	98	W	BSW	7.0	6.5 - 7.5	658	233	8	750	1655	50	340	500	A	A
		60	185/55R15	82	V	BSW	6.0	5.5 - 6.5	585	194	8	475	1050	44	300	500	A	A
			185/55R16	83	H	BSW	6.0	5.5 - 6.5	610	194	8	487	1070	44	300	500	A	A
			195/55R15	85	V	BSW	6.0	5.5 - 6.5	595	201	8	515	1140	44	300	500	A	A
			195/55R16	87	V	BSW	6.0	5.5 - 6.5	620	201	8	545	1200	44	300	500	A	A
			205/55R16	91	V	BSW	6.5	6.0 - 7.0	632	214	8	615	1355	44	300	500	A	A
65		215/55R16	93	V	BSW	7.0	6.5 - 7.5	642	226	8	650	1435	44	300	500	A	A	
		215/55ZR17	94	W	BSW	7.0	6.5 - 7.6	668	226	8	670	1480	44	300	500	A	A	
		185/60R15	84	H	BSW	5.5	5.0 - 6.0	603	189	8	500	1100	44	300	500	A	A	
		195/60R15	88	V	BSW	6.0	5.5 - 6.5	615	201	8	560	1230	44	300	500	A	A	
		205/60R15	91	V	BSW	6.0	5.5 - 6.5	627	209	8	615	1355	44	300	500	A	A	
		205/60R16	92	V	BSW	6.0	5.5 - 6.5	652	209	8	630	1390	44	300	500	A	A	
		215/60R16	95	V	BSW	6.5	6.0 - 7.0	664	221	8	690	1520	44	300	500	A	A	
70		225/60R16	98	V	BSW	6.5	6.0 - 7.5	676	228	8	750	1655	44	300	500	A	A	
		185/65R15	88	H	BSW	5.5	5.0 - 6.0	621	189	8	560	1230	44	300	500	A	A	
		195/65R15	91	H	BSW	6.0	5.5 - 6.5	635	201	8	615	1355	44	300	500	A	A	
		205/65R15	94	H	BSW	6.0	5.5 - 7.5	647	209	8	670	1480	44	300	500	A	A	
		205/65R16	95	V	BSW	6.0	5.5 - 7.5	672	209	8	690	1520	44	300	500	A	A	
215/65R15 XL		100	H	BSW	6.5	6.0 - 7.0	661	221	8	800	1765	50	340	500	A	A		

DEESTONE

MOVE THE WORLD



PATTERN NAME	SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		INFLATION PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
RA801E	30	255/30ZR19 XL 91	Y	BSW	9.0	8.5 - 9.5	635	256	7.6	615	1355	50	340	300	AA	A	
		275/30ZR19 XL 96	Y	BSW	9.5	9.0 - 10.0	646	274	7.6	710	1565	50	340	300	AA	A	
	35	235/35ZR19 XL 91	Y	BSW	8.5	8.0 - 9.0	645	237	7.6	615	1355	50	340	300	AA	A	
		245/35ZR18 XL 92	Y	BSW	8.5	8.0 - 9.0	626	244	7.6	630	1390	50	340	300	AA	A	
		245/35ZR19 XL 93	Y	BSW	8.5	8.0 - 9.0	652	244	7.6	650	1435	50	340	300	AA	A	
		255/35ZR18 XL 94	Y	BSW	9.0	8.5 - 9.5	633	256	7.6	670	1480	50	340	300	AA	A	
		255/35ZR19 XL 96	Y	BSW	9.0	8.5 - 9.5	659	256	7.6	710	1565	50	340	300	AA	A	
		255/35ZR20 XL 97	Y	BSW	9.0	8.5 - 9.5	684	256	7.6	730	1610	50	340	300	AA	A	
	40	265/35ZR18 XL 97	Y	BSW	9.5	9.0 - 10.0	640	267	7.6	730	1610	50	340	300	AA	A	
		275/35ZR20 XL 102	Y	BSW	9.5	9.0 - 10.0	698	274	7.6	850	1875	50	340	300	AA	A	
		315/35ZR20 XL 110	W	BSW	11.0	10.5 - 11.5	728	320	7.6	1060	2335	50	340	300	AA	A	
		205/40ZR17 XL 84	W	BSW	7.5	7.0 - 8.0	594	209	7.6	500	1100	50	340	300	AA	A	
		215/40ZR17 XL 87	W	BSW	7.5	7.0 - 8.0	601	215	7.6	545	1200	50	340	300	AA	A	
		215/40ZR18 XL 89	Y	BSW	7.5	7.0 - 8.0	626	215	7.6	580	1280	50	340	300	AA	A	
		225/40ZR18 XL 92	Y	BSW	8.0	7.5 - 8.5	637	230	7.6	630	1390	50	340	300	AA	A	
		235/40ZR18 XL 95	Y	BSW	8.5	8.0 - 9.0	642	237	7.6	690	1520	50	340	300	AA	A	
		235/40ZR19 XL 96	Y	BSW	8.5	8.0 - 9.0	668	237	7.6	710	1565	50	340	300	AA	A	
		245/40ZR17 XL 95	W	BSW	8.5	8.0 - 9.0	628	248	7.6	690	1520	50	340	300	AA	A	
	45	245/40ZR18 XL 97	Y	BSW	8.5	8.0 - 9.0	650	244	7.6	730	1610	50	340	300	AA	A	
		245/40ZR19 XL 98	Y	BSW	8.5	8.0 - 9.0	676	244	7.6	750	1655	50	340	300	AA	A	
		245/40ZR20 XL 99	Y	BSW	8.5	8.0 - 9.0	701	244	7.6	775	1710	50	340	300	AA	A	
		255/40ZR19 XL 100	Y	BSW	9.0	8.5 - 9.5	684	256	7.6	800	1765	50	340	300	AA	A	
		275/40ZR20 XL 106	Y	BSW	9.5	9.0 - 10.0	728	278	7.6	950	2095	50	340	300	AA	A	
		195/45ZR16 XL 84	W	BSW	6.5	6.0 - 7.0	582	195	7.6	500	1100	50	340	300	AA	A	
		205/45ZR16 XL 87	W	BSW	7.0	6.5 - 7.5	588	203	7.6	545	1200	50	340	300	AA	A	
		205/45ZR17 XL 88	W	BSW	7.0	6.5 - 7.5	614	203	7.6	560	1230	50	340	300	AA	A	
		215/45ZR16 XL 90	W	BSW	7.0	6.5 - 7.5	597	210	7.6	600	1320	50	340	300	AA	A	
		215/45ZR17 XL 91	W	BSW	7.0	6.5 - 7.5	623	210	7.6	615	1355	50	340	300	AA	A	
		225/45ZR17 XL 94	W	BSW	7.5	7.0 - 8.0	634	225	7.6	670	1480	50	340	300	AA	A	
		225/45ZR18 XL 95	Y	BSW	7.5	7.0 - 8.0	656	222	7.6	690	1520	50	340	300	AA	A	
		235/45ZR17 XL 97	W	BSW	8.0	7.5 - 8.5	644	236	7.6	730	1610	50	340	300	AA	A	
		235/45ZR18 XL 98	Y	BSW	8.0	7.5 - 8.5	666	232	7.6	750	1655	50	340	300	AA	A	
	235/45ZR19 XL 99	Y	BSW	8.0	7.5 - 8.5	691	232	7.6	775	1710	50	340	300	AA	A		
	50	245/45ZR17 XL 99	W	BSW	8.0	7.5 - 8.5	649	239	7.6	775	1710	50	340	300	AA	A	
		245/45ZR18 XL 100	Y	BSW	8.0	7.5 - 8.5	677	243	7.6	800	1765	50	340	300	AA	A	
		245/45ZR19 XL 102	Y	BSW	8.0	7.5 - 8.5	700	239	7.6	850	1875	50	340	300	AA	A	
		205/50ZR17 XL 93	W	BSW	6.5	6.0 - 7.0	638	214	7.6	650	1435	50	340	300	AA	A	
		215/50ZR17 XL 95	W	BSW	7.0	6.5 - 7.5	648	226	7.6	690	1520	50	340	300	AA	A	
		225/50ZR17 XL 98	W	BSW	7.0	6.5 - 7.5	658	233	7.6	750	1655	50	340	300	AA	A	
	55	235/50ZR18 XL 101	Y	BSW	7.5	7.0 - 8.0	690	241	7.6	825	1820	50	340	300	AA	A	
195/55R16 XL 91		V	BSW	6.0	5.5 - 6.5	617	198	7.6	615	1355	50	340	300	AA	A		
205/55ZR16 XL 94		W	BSW	6.5	6.0 - 7.0	632	214	7.6	670	1480	50	340	300	AA	A		
215/55ZR16 XL 97		W	BSW	7.0	6.5 - 7.5	642	226	7.6	730	1610	50	340	300	AA	A		
215/55ZR17 XL 98		W	BSW	7.0	6.5 - 7.5	668	226	7.6	750	1655	50	340	300	AA	A		
		225/55ZR17 XL 101	W	BSW	7.0	6.5 - 7.5	680	233	7.6	825	1820	50	340	300	AA	A	
		235/55ZR17 XL 103	Y	BSW	7.5	7.0 - 8.0	687	241	7.6	875	1930	50	340	300	AA	A	

LT - SUV

PAYAK R401

PAYAK R402

PAYAK R403

TITANZ T88

PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
R401	80	195R14C	106/104	P	8	BSW	5.5	5.0 - 6.0	666	198	9.0	950	2095	900	1985	65	450	-	-	-
R402	60	185/60R15C	94/92	T	6	BSW	5.5	5.0 - 6.0	603	197	9.4	670	1480	630	1390	54	375	-	-	-
		205/65R16C	107/105	R	8	BSW	6.0	5.5 - 6.5	672	209	9.1	975	2150	925	2040	69	475	-	-	-
	65	215/65R16C	109/107	R	8	BSW	6.5	6.0 - 7.0	686	221	9.4	1030	2270	975	2150	69	475	-	-	-
		235/65R16C	115/113	R	8	BSW	7.0	6.5 - 7.5	712	240	9.4	1215	2680	1150	2535	69	475	-	-	-
	70	195/70R15C	104/102	R	8	BSW	6.0	5.5 - 6.5	655	201	9.5	900	1985	850	1875	65	450	-	-	-
		205/70R15C	106/104	Q	8	BSW	6.0	5.5 - 6.5	669	209	9.5	950	2094	900	1984	65	450	-	-	-
		215/70R15C	109/107	R	8	BSW	6.5	6.0 - 7.0	683	221	9.5	1030	2270	975	2150	65	450	-	-	-
		225/70R15C	112/110	R	8	BSW	6.5	6.0 - 7.0	697	228	9.4	1120	2470	1060	2335	65	450	-	-	-
		255/70R15C	112/110	R	8	BSW	7.5	7.0 - 8.0	739	260	9.5	1120	2470	1060	2335	55	375	-	-	-
		195/75R16C	107/105	R	8	BSW	5.5	5.0 - 6.0	698	204	10.0	975	2150	925	2040	69	475	-	-	-
	75	205/75R16C	110/108	R	8	BSW	5.5	5.0 - 6.0	714	203	9.1	1060	2335	1000	2205	69	475	-	-	-
		215/75R16C	113/111	R	8	BSW	6.0	5.5 - 6.5	728	216	9.4	1150	2535	1090	2405	69	475	-	-	-
		225/75R16C	116/114	R	8	BSW	6.0	5.5 - 6.5	744	223	9.4	1250	2755	1180	2600	69	475	-	-	-
	R403	70	245/70R16	107	S	-	BSW	7.0	6.5 - 7.5	750	248	10.0	975	2149	-	-	44	300	-	-
225/70R15C			109/107	S	6	BSW	6.5	6.0 - 7.0	697	228	9.8	1030	2270	975	2150	55	375	-	-	-

PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
T88	65	215/65R16C	109/107	R	8	BSW	6.5	6.0 - 7.0	686	221	8.5	1030	2270	975	2150	69	475	-	-	-
	70	205/70R15C	106/104	Q	8	BSW	6.0	5.5 - 6.5	669	209	8.5	950	2094	900	1984	65	450	-	-	-
		215/70R15C	109/107	R	8	BSW	6.5	6.0 - 7.0	683	221	8.5	1030	2270	975	2150	65	450	-	-	-

PAYAK R404A/T

PAYAK R406

PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
R404	50	265/50R20	107	T	-	BSW	8.5	8.0 - 9.0	774	277	9.6	975	2150	-	-	44	300	540	A	B
	55	275/55R20 XL	117	T	-	BSW	8.5	8.0 - 9.0	810	284	9.6	1285	2835	-	-	50	340	540	A	B
		285/55R20	115	T	-	BSW	9.0	8.5 - 9.5	822	297	9.6	1215	2680	-	-	44	300	540	A	B
	60	265/60R18	110	T	-	BSW	8.0	7.5 - 8.5	775	272	9.6	1060	2335	-	-	44	300	540	A	B
		275/60R20	115	T	-	BSW	8.0	7.5 - 8.5	838	279	9.6	1215	2680	-	-	44	300	540	A	B
	65	245/65R17	107	T	-	BSW	7.0	6.5 - 7.5	750	248	9.6	975	2150	-	-	44	300	540	A	B
		265/65R17	112	T	-	BSW	8.0	7.5 - 8.5	776	272	9.6	1120	2470	-	-	44	300	540	A	B
	70	275/65R18	116	T	-	BSW	8.0	7.5 - 8.5	815	279	9.6	1250	2755	-	-	44	300	540	A	B
		LT265/70R17	121/118	S	10	BSW/OWL	8.0	7.5 - 8.5	804	272	12.0	1450	3195	1320	2910	80	550	-	-	-
		LT285/70R17	121/118	S	10	BSW/OWL	8.5	8.0 - 9.0	832	292	9.6	1450	3195	1320	2910	80	550	-	-	-
		235/70R16	106	T	-	BSW/OWL	7.0	6.5 - 7.5	736	240	9.6	950	2095	-	-	44	300	540	A	B
		245/70R16 XL	111	T	-	BSW	7.0	6.5 - 7.5	750	248	9.6	1090	2405	-	-	50	340	540	A	B
		245/70R17	110	T	-	BSW/OWL	7.0	6.5 - 7.5	776	248	9.6	1060	2335	-	-	44	300	540	A	B
		255/70R16	111	T	-	BSW/OWL	7.5	7.0 - 8.0	764	260	9.6	1090	2405	-	-	44	300	540	A	B
		265/70R16	112	T	-	BSW/OWL	8.0	7.5 - 8.5	778	272	9.6	1120	2470	-	-	44	300	540	A	B
		265/70R17	115	T	-	BSW/OWL	8.0	7.5 - 8.5	804	272	9.6	1215	2680	-	-	44	300	540	A	B
		265/70R18	116	T	-	BSW	8.0	7.5 - 8.5	829	272	9.6	1250	2755	-	-	44	300	540	A	B
	75	285/70R17	117	T	-	BSW/OWL	8.5	9.0 - 10.0	832	292	9.6	1285	2835	-	-	44	300	540	A	B
		LT225/75R16	115/112	S	10	BSW/OWL	6.0	5.5 - 6.5	744	223	11.0	1215	2680	1120	2470	80	550	-	-	-
		LT235/75R15	104/101	S	6	BSW/OWL	6.5	6.0 - 7.0	733	235	11.0	900	1985	825	1820	50	350	-	-	-
		LT245/75R16	120/116	S	10	BSW/OWL	7.0	6.5 - 7.5	774	248	12.0	1400	3085	1250	2755	80	550	-	-	-
		LT245/75R17	121/118	S	10	BSW	7.0	6.5 - 7.5	800	248	12.1	1450	3195	1320	2910	80	550	-	-	-
		LT265/75R16	123/120	S	10	BSW/OWL	7.5	7.0 - 8.0	804	267	12.0	1550	3415	1400	3085	80	550	-	-	-
		LT285/75R16	126/123	S	10	BSW/OWL	8.0	7.5 - 8.5	834	286	12.1	1700	3750	1550	3415	80	550	-	-	-
		235/75R15	105	T	-	BSW/OWL	6.5	6.0 - 7.0	733	235	9.6	925	2040	-	-	44	300	540	A	B
		245/75R16	111	T	-	BSW/OWL	7.0	6.5 - 7.5	774	248	9.6	1090	2405	-	-	44	300	540	A	B
		265/75R16	116	T	-	BSW/OWL	7.5	7.0 - 8.0	804	267	9.6	1250	2755	-	-	44	300	540	A	B
	80	LT235/80R17	120/117	S	10	BSW	6.5	6.0 - 7.0	808	235	12.1	1400	3085	1285	2835	80	550	-	-	-
		LT215/85R16	115/112	S	10	BSW/OWL	6.0	5.5 - 6.5	772	216	11.0	1215	2680	1120	2470	80	550	-	-	-
	85	LT235/85R16	120/116	S	10	BSW/OWL	6.5	6.0 - 7.0	806	235	12.0	1400	3085	1250	2755	80	550	-	-	-
30X9.50R15 LT		104	S	6	BSW/OWL	7.5	7.0 - 8.0	750	240	12.0	900	1985	-	-	50	350	-	-	-	
-	31X10.50R15 LT	109	S	6	BSW/OWL	8.5	8.0 - 9.0	775	268	12.0	1030	2270	-	-	50	350	-	-	-	
-	35X12.50R17 LT	121	S	10	BSW	10.0	9.5 - 10.5	877	318	12.0	1450	3195	-	-	65	450	-	-	-	
R406	-	5.50R13 LT	97/95	P	12	BSW	4.0	3.5 - 4.5	622	151	8.9	730	1610	690	1520	91	625	-	-	-
	-	5.00R12 LT	88/86	P	10	BSW	3.5	3.0 - 4.0	568	134	8.9	560	1230	530	1160	73	500	-	-	-
	-	5.50R12 LT	92/90	P	10	BSW	3.5	3.0 - 4.0	600	160	8.5	630	1390	530	1320	73	500	-	-	-

PAYAK 007 R601

PAYAK H/T R602

PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
R601	50	265/50R20	107	V		BSW	8.5	8.0 - 9.0	774	277	8.4	975	2150			44	300	560	A	A
		285/50R20	112	V	-	BSW	9.0	8.5 - 9.5	794	297	8.4	1120	2470	-	-	44	300	560	A	A
	55	225/55R17 XL	101	H	-	BSW	7.0	6.5 - 7.5	680	233	8.4	825	1820	-	-	50	340	560	A	A
		235/55R18 XL	104	V	-	BSW	7.5	7.0 - 8.0	715	245	8.4	900	1985	-	-	50	340	560	A	A
	55	255/55R18 XL	109	V	-	BSW	8.0	7.5 - 8.5	737	265	8.4	1030	2270	-	-	50	340	560	A	A
		275/55R20 XL	117	V	-	BSW	8.5	8.0 - 9.0	810	284	8.4	1285	2835	-	-	50	340	560	A	A
	55	225/55R18	98	V	-	BSW	7.0	6.5 - 7.5	705	233	8.4	750	1655	-	-	44	300	560	A	A
		265/60R18	110	H	-	BSW	8.0	7.5 - 8.5	775	272	8.4	1060	2335	-	-	44	300	560	A	A
	60	235/60R18 XL	107	V	-	BSW	7.0	6.5 - 7.5	739	240	8.4	975	2150	-	-	50	340	560	A	A
		275/60R20	115	H	-	BSW	8.0	7.5 - 8.5	838	279	8.4	1215	2680	-	-	44	340	560	A	A
	60	285/60R18	116	V	-	BSW	8.5	8.0 - 9.0	799	292	8.4	1250	2755	-	-	44	340	560	A	A
		245/60R18	105	V	-	BSW	7.0	6.5 - 7.5	751	248	8.4	925	2040	-	-	44	340	560	A	A
	60	225/60R18	100	H	-	BSW	6.5	6.0 - 7.0	727	228	8.4	800	1765	-	-	44	340	560	A	A
		235/60R17	102	H	-	BSW	7.0	6.5 - 7.5	714	240	8.4	850	1875	-	-	44	340	560	A	A
	60	225/60R17	99	H	-	BSW	6.5	6.0 - 7.0	702	228	8.4	775	1710	-	-	44	340	560	A	A
		225/65R17	102	H	-	BSW	6.5	6.0 - 7.0	724	228	8.4	850	1875	-	-	44	300	560	A	A
	65	235/65R17 XL	108	H	-	BSW	7.0	6.5 - 7.5	738	240	8.4	1000	2205	-	-	50	340	560	A	A
		245/65R17 XL	111	H	-	BSW	7.0	6.5 - 7.5	750	248	8.4	1090	2405	-	-	50	340	560	A	A
	65	265/65R17	112	H	-	BSW/OWL	8.0	7.5 - 8.5	776	272	8.4	1120	2470	-	-	44	300	560	A	A
		275/65R18	116	H	-	BSW	8.0	7.5 - 8.5	815	279	8.4	1250	2755	-	-	44	300	560	A	A
	65	215/65R16 XL	102	H	-	BSW	6.5	6.0 - 7.0	686	221	8.4	850	1875	-	-	50	340	560	A	A
		255/65R18	111	H	-	BSW	7.5	7.0 - 8.0	789	260	8.4	1090	2405	-	-	44	340	560	A	A
	65	285/65R17	116	H	-	BSW	8.5	8.0 - 9.0	802	292	8.4	1250	2755	-	-	44	340	560	A	A
		205/70R14 XL	98	H	-	BSW	6.0	5.5 - 6.5	644	209	8.2	750	1655	-	-	50	340	560	A	A
	70	205/70R15	96	H	-	BSW	6.0	5.5 - 6.5	669	209	8.2	710	1565	-	-	44	300	560	A	A
		215/70R15	98	H	-	BSW	6.5	6.0 - 7.0	683	221	8.2	750	1655	-	-	44	300	560	A	A
	70	215/70R16	100	H	-	BSW	6.5	6.0 - 7.0	708	221	8.4	800	1765	-	-	44	300	560	A	A
		225/70R15	100	H	-	BSW	6.5	6.0 - 7.0	697	228	8.4	800	1765	-	-	44	300	560	A	A
	70	225/70R16	103	H	-	BSW	6.5	6.0 - 7.0	722	228	8.4	875	1930	-	-	44	300	560	A	A
		235/70R16	106	H	-	BSW	7.0	6.5 - 7.5	736	240	8.4	950	2095	-	-	44	300	560	A	A
	70	235/70R17 XL	111	H	-	BSW	7.0	6.5 - 7.5	762	240	8.4	1090	2405	-	-	50	340	560	A	A
		245/70R16 XL	111	H	-	BSW	7.0	6.5 - 7.5	750	248	8.4	1090	2405	-	-	50	340	560	A	A
	70	245/70R17	110	H	-	BSW	7.0	6.5 - 7.5	776	248	8.4	1060	2335	-	-	44	300	560	A	A
		265/70R16	112	H	-	BSW/OWL	8.0	7.5 - 8.5	778	272	8.4	1120	2470	-	-	44	300	560	A	A
	70	265/70R17	115	H	-	BSW	8.0	7.5 - 8.5	804	272	8.4	1215	2680	-	-	44	300	560	A	A
		265/70R18	116	H	-	BSW	8.0	7.5 - 8.5	829	272	8.4	1250	2755	-	-	44	300	560	A	A
	70	255/70R18	113	H	-	BSW	7.5	7.0 - 8.0	815	260	8.4	1150	2535	-	-	44	300	560	A	A
		255/70R16	111	H	-	BSW	7.5	7.0 - 8.0	764	260	8.4	1090	2405	-	-	44	300	560	A	A
	70	235/70R15	103	H	-	BSW	7.0	6.5 - 7.5	711	240	8.4	875	1930	-	-	44	300	560	A	A
		235/75R15 XL	109	T	-	BSW	6.5	6.0 - 7.0	733	235	8.4	1030	2270	-	-	50	340	560	A	A
75	225/75R15	102	T	-	BSW	6.0	5.5 - 6.5	719	223	8.4	850	1875	-	-	44	300	560	A	A	
	265/75R16	116	T	-	BSW	7.5	7.0 - 8.0	804	267	8.4	1250	2755	-	-	44	300	560	A	A	
75	245/75R16	111	T	-	BSW	7.0	6.5 - 7.5	774	248	8.4	1090	2405	-	-	44	300	560	A	A	
	225/75R16 XL	108	T	-	BSW	6.0	5.5 - 6.5	744	223	8.4	1000	2205	-	-	50	340	560	A	A	
75	215/75R15	100	T	-	BSW	6.0	5.5 - 6.5	703	216	8.4	800	1765	-	-	44	300	560	A	A	
	60	285/60R18	116	H	-	BSW	8.5	8.0 - 9.0	799	292	10.0	1250	2755	-	-	44	300	560	A	A
R602	65	285/65R17	116	H	-	BSW	8.5	8.0 - 9.0	802	292	10.0	1250	2755	-	-	44	300	560	A	A
	65	275/65R17	115	T	-	BSW	8.0	7.5 - 8.5	790	279	10.0	1215	2680	-	-	44	300	560	A	A
70	275/70R16	114	T	-	BSW	8.0	7.5 - 8.5	792	279	10.0	1180	2600	-	-	44	300	560	A	A	

EXPEDITE HP 100**R200****PAYAK HT603**

PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
HP100	35	295/35ZR21 XL	107	Y	-	BSW	10.5	10 - 11	736	296	7.8	975	2150	-	-	50	340	360	A	A
		315/35ZR20 XL	110	W	-	BSW	11.0	10.5 - 11.5	725	315	7.8	1060	2335	-	-	50	340	360	A	A
		285/35ZR22 XL	106	W	-	BSW	10.0	9.5 - 10.5	756	286	7.8	950	2095	-	-	50	340	360	A	A
	40	275/40ZR20 XL	106	Y	-	BSW	9.5	9 - 10	725	274	7.8	950	2095	-	-	50	340	360	A	A
		255/45R20 XL	105	V	-	BSW	8.5	8 - 9	734	251	7.8	925	2040	-	-	50	340	360	A	A
	45	275/45ZR19 XL	108	W	-	BSW	9.0	8.5 - 9.5	727	269	7.8	1000	2205	-	-	50	340	360	A	A
		275/45R20 XL	110	V	-	BSW	9.0	8.5 - 9.5	752	269	7.8	1060	2335	-	-	50	340	360	A	A
		285/45ZR19 XL	111	V	-	BSW	9.5	9 - 10	736	281	7.8	1090	2405	-	-	50	340	360	A	A
	55	215/55R18 XL	99	V	-	BSW	7.0	6.5 - 7.5	690	223	7.8	775	1710	-	-	50	340	360	A	A
		235/55ZR18 XL	104	W	-	BSW	7.5	7 - 8	712	241	7.8	900	1985	-	-	50	340	360	A	A
	60	215/60R16 XL	99	V	-	BSW	6.5	6 - 7	660	218	7.8	775	1710	-	-	50	340	360	A	A
		215/60R17 XL	100	V	-	BSW	6.5	6 - 7	686	218	8.0	800	1765	-	-	50	340	360	A	A
		235/60R18 XL	107	V	-	BSW	7.0	6.5 - 7.5	735	236	8.0	975	2150	-	-	50	340	360	A	A
	65	215/65R16 XL	102	V	-	BSW	6.5	6 - 7	681	218	7.8	850	1875	-	-	50	340	360	A	A
R200	80	155R12C	88/86	R	8	BSW	4.5	4.0 - 5.0	550	157	7.6	560	1235	530	1170	65	450	-	-	-
HT603	50	265/50R20 XL	112	V	-	BSW	8.5	8.0-9.0	774	277	8.5	1120	2470	-	-	50	340	560	A	A
		285/50R20	112	V	-	BSW	9.0	8.5-9.5	794	297	8.5	1120	2470	-	-	44	300	560	A	A
	55	235/55R18 XL	104	V	-	BSW	7.5	7.0-8.0	715	245	8.5	900	1985	-	-	50	340	560	A	A
		255/55R18 XL	109	V	-	BSW	8.0	7.5-8.5	737	265	8.5	1030	2270	-	-	50	340	560	A	A
		275/55R20 XL	117	V	-	BSW	8.5	8.0-9.0	810	284	8.5	1285	2835	-	-	50	340	560	A	A
	60	265/60R18	110	H	-	BSW	8.0	7.5-8.5	775	272	8.5	1060	2335	-	-	44	300	560	A	A
		225/65R17	102	H	-	BSW	6.5	6.0-7.0	724	228	8.5	850	1875	-	-	44	300	560	A	A
	65	245/65R17 XL	111	H	-	BSW	7.0	6.5-7.5	750	248	8.5	1090	2405	-	-	50	340	560	A	A
		235/65R17 XL	108	H	-	BSW	7.0	6.5-7.5	738	240	8.5	1000	2205	-	-	50	340	560	A	A
		265/65R17	112	H	-	BSW	8.0	7.5-8.5	776	272	8.5	1120	2470	-	-	44	300	560	A	A
	70	235/70R16	106	H	-	BSW	7.0	6.5-7.5	736	240	8.5	950	2095	-	-	44	300	560	A	A
		265/70R16	112	H	-	BSW	8.0	7.5-8.5	778	272	8.5	1120	2470	-	-	44	300	560	A	A
		245/70R16 XL	111	H	-	BSW	7.0	6.5-7.5	750	248	8.5	1090	2405	-	-	50	340	560	A	A
		245/70R17	110	H	-	BSW	7.0	6.5-7.5	776	248	8.5	1060	2335	-	-	44	300	560	A	A
		215/70R16	100	H	-	BSW	6.5	6.0-7.0	708	221	8.5	800	1765	-	-	44	300	560	A	A
		225/70R16	103	H	-	BSW	6.5	6.0-7.0	722	228	8.5	875	1930	-	-	44	300	560	A	A
		215/70R15	98	H	-	BSW	6.5	6.0-7.0	683	221	8.5	750	1655	-	-	44	300	560	A	A
		235/70R17 XL	111	H	-	BSW	7.0	6.5-7.5	762	240	8.5	1090	2405	-	-	50	340	560	A	A
		225/70R15	100	H	-	BSW	6.5	6.0-7.0	697	228	8.5	800	1765	-	-	44	300	560	A	A
		205/70R15	96	H	-	BSW	6.0	5.5-6.5	669	209	8.5	710	1565	-	-	44	300	560	A	A
75	265/70R17	115	H	-	BSW	8.0	7.5-8.5	804	272	8.5	1215	2680	-	-	44	300	560	A	A	
265/75R16	116	T	-	BSW	7.5	7.0-8.0	804	267	8.5	1250	2755	-	-	44	300	560	A	A		

KACHA R101

KACHA R102

ST RADIAL R501

PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
R101	80	165R13C	94/92	R	8	BSW	4.5	4.0 - 5.0	596	167	8.2	670	1480	630	1390	65	450	-	-	-
		185R14C	102/100	Q	8	BSW	5.5	5.0 - 6.0	650	188	8.6	850	1874	800	1764	65	450	-	-	-
		195R14C	106/104	P	8	BSW/WSW	5.5	5.0 - 6.0	666	198	9.0	950	2094	900	1984	65	450	-	-	-
		195R15C	106/104	P	8	BSW	5.5	5.0 - 6.0	690	198	9.0	950	2094	900	1984	65	450	-	-	-
		205R14C	109/107	P	8	BSW	6.0	5.5 - 6.5	686	208	9.0	1030	2270	975	2150	65	450	-	-	-
		205R16C	110/108	R	8	BSW	6.0	5.5 - 6.5	736	208	9.5	1060	2335	1000	2205	65	450	-	-	-
R102	80	195R14	106/104	R	8	BSW	5.5	5.0 - 6.0	666	198	9.0	950	2095	900	1985	65	450	-	-	-

PATTERN NAME	SERIES	SIZES	LOAD RANGE	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
R501	75	ST205/75R14	C	6	BSW	5.5	5.0 - 6.0	664	203	7.2	800	1760	710	1570	50	350	-	-	-
		ST205/75R14	D	8	BSW	5.5	5.0 - 6.0	664	203	7.2	925	2040	825	1820	65	450	-	-	-
		ST205/75R15	C	6	BSW	5.5	5.0 - 6.0	689	203	7.2	825	1820	730	1610	50	350	-	-	-
		ST205/75R15	D	8	BSW	5.5	5.0 - 6.0	689	203	7.2	975	2150	850	1870	65	450	-	-	-
		ST215/75R14	C	6	BSW	6.0	5.5 - 6.5	678	216	7.2	850	1870	750	1650	50	350	-	-	-
		ST225/75R15	D	8	BSW	6.0	5.5 - 6.5	719	223	7.2	1150	2450	1000	2200	65	450	-	-	-
	ST225/75R15	E	10	BSW	6.0	5.5 - 6.5	719	223	7.2	1285	2830	1120	2470	80	550	-	-	-	
	80	ST235/80R16	E	10	BSW	6.5	6.0 - 7.0	782	235	7.8	1550	3420	1360	3000	80	550	-	-	-
		ST235/80R16	F	12	BSW	6.5	6.0 - 7.0	782	235	7.8	1650	3630	1450	3195	95	650	-	-	-
		ST175/80R13	C	6	BSW	5.0	4.5 - 5.5	610	177	7.0	615	1360	545	1200	50	350	-	-	-



PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
R405	70	LT 265/70R17	121/118	Q	10	BSW/OWL	8.0	7.5 - 8.5	810	272	14.0	1450	3195	1320	2910	80	550	-	-	-
		LT 285/70R17	121/118	Q	10	BSW/OWL	8.5	8.0 - 9.0	838	292	15.0	1450	3195	1320	2910	80	550	-	-	-
	75	LT 285/75R16	126/123	Q	10	BSW/OWL	8.0	7.5 - 8.5	840	286	14.0	1700	3750	1550	3415	80	550	-	-	-
		LT 265/75R16	123/120	Q	10	BSW/OWL	7.5	7.0 - 8.0	810	267	14.0	1550	3415	1400	3085	80	550	-	-	-
		LT 245/75R16	120/116	Q	10	BSW/OWL	7.0	6.5 - 7.5	780	248	14.0	1400	3085	1250	2755	80	550	-	-	-
		LT 235/75R15	104/101	Q	6	BSW/OWL	6.5	6.0 - 7.0	739	235	15.0	900	1985	852	1820	50	350	-	-	-
		LT 245/75R17	121/118	Q	10	BSW/OWL	7.0	6.5 - 7.5	806	248	15.0	1450	3195	1320	2910	80	550	-	-	-
		85	LT 235/85R16	120/116	Q	10	BSW/OWL	6.5	6.0 - 7.0	812	235	15.0	1400	3085	1250	2755	80	550	-	-
	-	33X12.50R15 LT	108	Q	6	BSW/OWL	10.0	9.5 - 10.5	832	318	16.0	1000	2205	-	-	35	250	-	-	-
		31X10.50R15 LT	109	Q	6	BSW/OWL	8.5	8.0 - 9.0	781	268	14.0	1030	2270	-	-	50	350	-	-	-
		30X9.50R15 LT	104	Q	6	BSW/OWL	7.5	7.0 - 8.0	756	240	15.0	900	1985	-	-	50	350	-	-	-
		35X12.50R18 LT	123	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.0	1550	3415	-	-	65	450	-	-	-
		33X12.50R18 LT	118	Q	10	BSW	10.0	9.5 - 10.5	832	318	16.0	1320	2910	-	-	65	450	-	-	-
	35X12.50R20 LT	121	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.0	1450	3195	-	-	65	450	-	-	-	
R408	55	LT 305/55R20	121/118	Q	10	BSW	9.5	9.0 - 10.0	850	316	16.0	1450	3195	1320	2910	65	450	-	-	-
	65	LT 275/65R18	123/120	Q	10	BSW	8.0	7.5 - 8.5	821	279	16.0	1550	3415	1400	3085	80	550	-	-	-
	70	LT 275/70R18	125/122	Q	10	BSW	8.0	7.5 - 8.5	849	279	15.2	1650	3640	1500	3305	80	550	-	-	-
		LT 295/70R17	121/118	Q	10	BSW	8.5	8.0 - 9.0	852	299	16.7	1450	3195	1320	2910	80	550	-	-	-
		LT 285/70R17	121/118	Q	10	BSW	8.5	8.0 - 9.0	838	292	15.2	1450	3195	1320	2910	80	550	-	-	-
		LT 265/70R17	121/118	Q	10	BSW	8.0	7.5 - 8.5	810	272	15.2	1450	3195	1320	2910	80	550	-	-	-
		LT 305/70R18	126/123	Q	10	BSW	9.0	8.5 - 9.5	891	311	16.0	1700	3750	1550	3415	65	450	-	-	-
		LT 315/70R17	121/118	Q	8	BSW	9.5	9.0 - 10.0	880	323	16.0	1450	3195	1320	2910	50	350	-	-	-
	75	LT 245/75R17	121/118	Q	10	BSW	7.0	6.5 - 7.5	806	248	15.0	1450	3195	1320	2910	80	550	-	-	-
		LT 285/75R16	126/123	Q	10	BSW	8.0	7.5 - 8.5	840	286	15.2	1700	3750	1550	3415	80	550	-	-	-
		LT 265/75R16	123/120	Q	10	BSW	7.5	7.0 - 8.0	810	267	15.2	1550	3415	1400	3085	80	550	-	-	-
		LT 245/75R16	120/116	Q	10	BSW	7.0	6.5 - 7.5	780	248	15.2	1400	3085	1250	2755	80	550	-	-	-
		LT 235/75R15	104/101	Q	6	BSW	6.5	6.0 - 7.0	739	235	14.7	900	1985	825	1820	50	350	-	-	-
		LT 315/75R16	121/118	Q	8	BSW	8.5	8.0 - 9.0	884	313	16.0	1450	3195	1320	2910	50	350	-	-	-
	80	LT 235/80R17	120/117	Q	10	BSW	6.5	6.0 - 7.0	814	235	16.0	1400	3085	1285	2835	80	550	-	-	-
	85	LT 235/85R16	120/116	Q	10	BSW	6.5	6.0 - 7.0	812	235	15.0	1400	3085	1250	2755	80	550	-	-	-
	-	33X12.50R15 LT	108	Q	6	BSW	10.0	9.5 - 10.5	832	318	16.7	1000	2205	-	-	35	250	-	-	-
		31X10.50R15 LT	109	Q	6	BSW	8.5	8.0 - 9.0	781	268	14.7	1030	2270	-	-	50	350	-	-	-
		30X9.50R15 LT	104	Q	6	BSW	7.5	7.0 - 8.0	756	240	14.7	900	1985	-	-	50	350	-	-	-
		32X11.50R15 LT	113	Q	6	BSW	9.0	8.5 - 9.5	807	290	16.7	1150	2535	-	-	50	350	-	-	-
		35X12.50R15 LT	113	Q	6	BSW	10.0	9.5 - 10.5	883	318	16.7	1150	2535	-	-	35	250	-	-	-
		33X12.50R17 LT	114	Q	8	BSW	10.0	9.5 - 10.5	832	318	16.7	1180	2600	-	-	50	350	-	-	-
		35X12.50R17 LT	121	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.7	1450	3195	-	-	65	450	-	-	-
37X12.50R17 LT		124	Q	8	BSW	10.0	9.5 - 10.5	934	318	16.7	1600	3525	-	-	50	350	-	-	-	
35X12.50R18 LT		123	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.7	1550	3415	-	-	65	450	-	-	-	
33X12.50R18 LT		118	Q	10	BSW	10.0	9.5 - 10.5	832	318	16.7	1320	2910	-	-	65	450	-	-	-	
35X12.50R20 LT		121	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.7	1450	3195	-	-	65	450	-	-	-	
33X12.50R20 LT		114	Q	10	BSW	10.0	9.5 - 10.5	832	318	15.2	1180	2600	-	-	65	450	-	-	-	
37x12.50R20 LT		126	Q	10	BSW	10.0	9.5 - 10.5	934	318	16.7	1700	3750	-	-	65	450	-	-	-	
35X12.50R22 LT		117	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.7	1285	2835	-	-	65	450	-	-	-	
37x13.50R22 LT	123	Q	10	BSW	11.0	10.5 - 11.5	934	345	16.7	1550	3415	-	-	65	450	-	-	-		
33x12.50R22 LT	109	Q	10	BSW	10.0	9.5 - 10.5	832	318	16.7	1030	2270	-	-	65	450	-	-	-		



DEESTONE CORPORATION LIMITED

84 Soi Petchkasem 122 , Moo7, Petchkasem Rd. , Oamnoi , Krathumban,
Samutsakorn, 74130, THAILAND

Tel : (+662) 420-0038 , 023-4756

Fax : (+662) 420-0572 , 023-4724

E-mail : deestone@deestone.com



www.facebook.com/Deestonetyre



www.deestone.com



Deestonetyre

